

REPORT NUMBER: 703

MSDS NO: MZC0357

MAINFRAME UPLOAD DATE: 03/04/05

UNIVAR USA INC.
MATERIAL SAFETY DATA SHEET

PAGE: 001

VERSION: 004

PRODUCT: CALCIUM CHLORIDE SOLID
HARDNESS

ORDER NO: 343354
PROD NO : 743158

N JONAS CO.
4525 ADAMS CIRCLE
CALCIUM CHLOIDE MATERIAL

BENSALEM ,PA 198200425

UNIVAR USA INC.
17425 NE UNION HILL RD , REDMOND

(425)889-3400
, WA 98052

----- EMERGENCY ASSISTANCE -----

FOR EMERGENCY ASSISTANCE INVOLVING CHEMICALS CALL - CHEMTREC
(800)424-9300

PRODUCT NAME: CALCIUM CHLORIDE SOLID / HARDNESS
MSDS NUMBER: MZC0357
DATE ISSUED: 3/4/2005
SUPERSEDES: 8/12/2004
ISSUED BY: 008614

=====
CALCIUM CHLORIDE
=====

1. PRODUCT IDENTIFICATION

SYNONYMS: CALCIUM DICHLORIDE; CALCIUM CHLORIDE ANHYDROUS;
CALTAC(R); DOWFLAKE
CAS NO: 10043-52-4
MOLECULAR WEIGHT: 110.98
CHEMICAL FORMULA: CaCl2
DISTRIBUTED BY:
UNIVAR USA INC.
17425 NE UNION HILL ROAD
REDMOND, WA 98052

PRODUCT: CALCIUM CHLORIDE SOLID

ORDER NO: 343354

PROD NO : 743158

425-889-3400
=====

2. COMPOSITION/INFORMATION ON INGREDIENTS

INGREDIENT	CAS NO	PERCENT	HAZARDOUS
CALCIUM CHLORIDE	10043-52-4	93 - 100%	YES

=====

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

WARNING! CAUSES IRRITATION TO SKIN, EYES AND RESPIRATORY TRACT. HARMFUL IF SWALLOWED OR INHALED.

POTENTIAL HEALTH EFFECTS

INHALATION:

GRANULAR MATERIAL DOES NOT POSE A SIGNIFICANT INHALATION HAZARD, BUT INHALATION OF DUST MAY CAUSE IRRITATION TO THE RESPIRATORY TRACT, WITH SYMPTOMS OF COUGHING AND SHORTNESS OF BREATH.

INGESTION:

LOW TOXICITY MATERIAL BUT INGESTION MAY CAUSE SERIOUS IRRITATION OF THE MUCOUS MEMBRANE DUE TO HEAT OF HYDROLYSIS. LARGE AMOUNTS CAN CAUSE GASTROINTESTINAL UPSET, VOMITING, ABDOMINAL PAIN.

SKIN CONTACT:

SOLID MAY CAUSE MILD IRRITATION ON DRY SKIN; STRONG SOLUTIONS OR SOLID IN CONTACT WITH MOIST SKIN MAY CAUSE SEVERE IRRITATION, EVEN BURNS.

EYE CONTACT:

HAZARD MAY BE EITHER MECHANICAL ABRASION OR, MORE SERIOUS, BURNS FROM HEAT OF HYDROLYSIS AND CHLORIDE IRRITATION.

CHRONIC EXPOSURE:

NO INFORMATION FOUND.

AGGRAVATION OF PRE-EXISTING CONDITIONS:

NO INFORMATION FOUND.
=====

PRODUCT: CALCIUM CHLORIDE SOLID

ORDER NO: 343354

PROD NO : 743158

4. FIRST AID MEASURES

INHALATION:

REMOVE TO FRESH AIR. IF NOT BREATHING, GIVE ARTIFICIAL RESPIRATION. IF BREATHING IS DIFFICULT, GIVE OXYGEN. GET MEDICAL ATTENTION.

INGESTION:

INDUCE VOMITING IMMEDIATELY AS DIRECTED BY MEDICAL PERSONNEL. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON. GET MEDICAL ATTENTION.

SKIN CONTACT:

WIPE OFF EXCESS MATERIAL FROM SKIN THEN IMMEDIATELY FLUSH SKIN WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES. REMOVE CONTAMINATED CLOTHING AND SHOES. GET MEDICAL ATTENTION. WASH CLOTHING BEFORE REUSE. THOROUGHLY CLEAN SHOES BEFORE REUSE.

EYE CONTACT:

IMMEDIATELY FLUSH EYES WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES, LIFTING LOWER AND UPPER EYELIDS OCCASIONALLY. GET MEDICAL ATTENTION IMMEDIATELY.

NOTE TO PHYSICIAN:

ORAL INGESTION MAY CAUSE SERUM ACIDOSIS.

=====

5. FIRE FIGHTING MEASURES

FIRE:

NOT CONSIDERED TO BE A FIRE HAZARD.

EXPLOSION:

NOT CONSIDERED TO BE AN EXPLOSION HAZARD.

FIRE EXTINGUISHING MEDIA:

USE ANY MEANS SUITABLE FOR EXTINGUISHING SURROUNDING FIRE.

SPECIAL INFORMATION:

IN THE EVENT OF A FIRE, WEAR FULL PROTECTIVE CLOTHING AND NIOSH-APPROVED SELF-CONTAINED BREATHING APPARATUS WITH FULL FACEPIECE OPERATED IN THE PRESSURE DEMAND OR OTHER POSITIVE PRESSURE MODE. AT HIGH TEMPERATURES OR WHEN MOISTENED UNDER FIRE CONDITIONS, CALCIUM CHLORIDE MAY PRODUCE TOXIC OR IRRITATING FUMES.

=====

6. ACCIDENTAL RELEASE MEASURES

PRODUCT: CALCIUM CHLORIDE SOLID

ORDER NO: 343354

PROD NO : 743158

VENTILATE AREA OF LEAK OR SPILL. WEAR APPROPRIATE PERSONAL PROTECTIVE EQUIPMENT AS SPECIFIED IN SECTION 8. SPILLS: SWEEP UP AND CONTAINERIZE FOR RECLAMATION OR DISPOSAL. VACUUMING OR WET SWEEPING MAY BE USED TO AVOID DUST DISPERSAL. SMALL AMOUNTS OF RESIDUE MAY BE FLUSHED TO SEWER WITH PLENTY OF WATER.

=====

7. HANDLING AND STORAGE

KEEP IN A TIGHTLY CLOSED CONTAINER, STORED IN A COOL, DRY, VENTILATED AREA. PROTECT AGAINST PHYSICAL DAMAGE. MOIST CALCIUM CHLORIDE AND CONCENTRATED SOLUTIONS CAN CORRODE STEEL. WHEN EXPOSED TO THE ATMOSPHERE, CALCIUM CHLORIDE WILL ABSORB WATER AND FORM A SOLUTION. CONTAINERS OF THIS MATERIAL MAY BE HAZARDOUS WHEN EMPTY SINCE THEY RETAIN PRODUCT RESIDUES (DUST, SOLIDS); OBSERVE ALL WARNINGS AND PRECAUTIONS LISTED FOR THE PRODUCT.

=====

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

AIRBORNE EXPOSURE LIMITS:
NONE ESTABLISHED.

VENTILATION SYSTEM:

A SYSTEM OF LOCAL AND/OR GENERAL EXHAUST IS RECOMMENDED TO KEEP EMPLOYEE EXPOSURES AS LOW AS POSSIBLE. LOCAL EXHAUST VENTILATION IS GENERALLY PREFERRED BECAUSE IT CAN CONTROL THE EMISSIONS OF THE CONTAMINANT AT ITS SOURCE, PREVENTING DISPERSION OF IT INTO THE GENERAL WORK AREA. PLEASE REFER TO THE ACGIH DOCUMENT, "INDUSTRIAL VENTILATION, A MANUAL OF RECOMMENDED PRACTICES", MOST RECENT EDITION, FOR DETAILS.

PERSONAL RESPIRATORS (NIOSH APPROVED):

FOR CONDITIONS OF USE WHERE EXPOSURE TO DUST OR MIST IS APPARENT AND ENGINEERING CONTROLS ARE NOT FEASIBLE, A PARTICULATE RESPIRATOR (NIOSH TYPE N95 OR BETTER FILTERS) MAY BE WORN. IF OIL PARTICLES (E.G. LUBRICANTS, CUTTING FLUIDS, GLYCERINE, ETC.) ARE PRESENT, USE A NIOSH TYPE R OR P FILTER. FOR EMERGENCIES OR INSTANCES WHERE THE EXPOSURE LEVELS ARE NOT KNOWN, USE A FULL-FACE POSITIVE-PRESSURE, AIR-SUPPLIED RESPIRATOR.

WARNING: AIR-PURIFYING RESPIRATORS DO NOT PROTECT WORKERS IN OXYGEN-DEFICIENT ATMOSPHERES.

SKIN PROTECTION:

WEAR PROTECTIVE GLOVES AND CLEAN BODY-COVERING CLOTHING.

EYE PROTECTION:

USE CHEMICAL SAFETY GOGGLES AND/OR FULL FACE SHIELD WHERE DUSTING OR

PRODUCT: CALCIUM CHLORIDE SOLID

ORDER NO: 343354

PROD NO : 743158

SPLASHING OF SOLUTIONS IS POSSIBLE. MAINTAIN EYE WASH FOUNTAIN AND QUICK-DRENCH FACILITIES IN WORK AREA.

OTHER CONTROL MEASURES:

MAINTAIN GOOD HOUSEKEEPING IN WORK AREA. DUST DEPOSITS ON FLOORS AND OTHER SURFACES MAY PICK UP MOISTURE AND CAUSE THE SURFACES TO BECOME SLIPPERY AND PRESENT SAFETY HAZARDS.

9. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE:

WHITE OR GRAY-WHITE GRANULES.

BOILING POINT:

> 1600C (> 2912F)

ODOR:

ODORLESS.

MELTING POINT:

772C (1422F)

SOLUBILITY:

FREELY SOLUBLE IN WATER, EXOTHERMIC.

VAPOR DENSITY (AIR=1):

NO INFORMATION FOUND.

DENSITY:

2.15

VAPOR PRESSURE (MM HG):

NO INFORMATION FOUND.

PH:

8 - 9 AQUEOUS SOLUTION

EVAPORATION RATE (BUAC=1):

NO INFORMATION FOUND.

% VOLATILES BY VOLUME @ 21C (70F):

0

10. STABILITY AND REACTIVITY

STABILITY:

STABLE UNDER ORDINARY CONDITIONS OF USE AND STORAGE. SUBSTANCE WILL PICK UP MOISTURE FROM THE AIR AND GO INTO SOLUTION IF EXPOSED IN OPEN CONTAINERS.

HAZARDOUS DECOMPOSITION PRODUCTS:

EMITS TOXIC CHLORINE FUMES WHEN HEATED TO DECOMPOSITION. MAY FORM HYDROGEN CHLORIDE IN PRESENCE OF SULFURIC OR PHOSPHORIC ACIDS OR WITH WATER AT ELEVATED TEMPERATURES.

HAZARDOUS POLYMERIZATION:

WILL NOT OCCUR.

INCOMPATIBILITIES:

PRODUCT: CALCIUM CHLORIDE SOLID

ORDER NO: 343354

PROD NO : 743158

METHYL VINYL ETHER, WATER, ZINC, BROMINE TRIFLUORIDE, MIXTURES OF LIME AND BORIC ACID, BARIUM CHLORIDE, AND 2-FURAN PERCARBOXYLIC ACID. METALS WILL SLOWLY CORRODE IN AQUEOUS CALCIUM CHLORIDE SOLUTIONS. ALUMINUM (AND ALLOYS) AND YELLOW BRASS WILL BE ATTACKED BY CALCIUM CHLORIDE.

CONDITIONS TO AVOID:
INCOMPATIBLES.

11. TOXICOLOGICAL INFORMATION

ORAL RAT LD50: 1000 MG/KG. INVESTIGATED AS A TUMORIGEN AND MUTAGEN.

-----CANCER LISTS-----

INGREDIENT	---NTP CARCINOGEN---		IARC CATEGORY
	KNOWN	ANTICIPATED	
CALCIUM CHLORIDE (10043-52-4)	NO	NO	NONE

12. ECOLOGICAL INFORMATION

ENVIRONMENTAL FATE:

BASED ON AVAILABLE INFORMATION FOR CALCIUM CHLORIDE ANHYDROUS, THIS MATERIAL WILL NOT BIODEGRADE OR BIOACCUMULATE.

ENVIRONMENTAL TOXICITY:

THE LC50/96-HOUR VALUES FOR FISH ARE OVER 100 MG/L.

13. DISPOSAL CONSIDERATIONS

WHATEVER CANNOT BE SAVED FOR RECOVERY OR RECYCLING SHOULD BE MANAGED IN AN APPROPRIATE AND APPROVED WASTE DISPOSAL FACILITY. PROCESSING, USE OR CONTAMINATION OF THIS PRODUCT MAY CHANGE THE WASTE MANAGEMENT OPTIONS. STATE AND LOCAL DISPOSAL REGULATIONS MAY DIFFER FROM FEDERAL DISPOSAL REGULATIONS.

DISPOSE OF CONTAINER AND UNUSED CONTENTS IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL REQUIREMENTS.

14. TRANSPORT INFORMATION

NOT REGULATED.

PRODUCT: CALCIUM CHLORIDE SOLID

ORDER NO: 343354
PROD NO : 743158

15. REGULATORY INFORMATION

-----CHEMICAL INVENTORY STATUS - PART 1-----

INGREDIENT	TSCA	EC	JAPAN	AUSTRALIA
CALCIUM CHLORIDE (10043-52-4)	YES	YES	YES	YES

-----CHEMICAL INVENTORY STATUS - PART 2-----

INGREDIENT	KOREA	DSL	NDL	PHIL.
CALCIUM CHLORIDE (10043-52-4)	YES	YES	NO	YES

-----FEDERAL, STATE & INTERNATIONAL REGULATIONS - PART 1-----

INGREDIENT	-SARA 302- RQ	TPQ	LIST	-SARA 313- CHEMICAL CATG
CALCIUM CHLORIDE (10043-52-4)	NO	NO	NO	NO

-----FEDERAL, STATE & INTERNATIONAL REGULATIONS - PART 2-----

INGREDIENT	CERCLA	-RCRA- 261.33	-TSCA- 8(D)
CALCIUM CHLORIDE (10043-52-4)	NO	NO	NO

CHEMICAL WEAPONS CONVENTION: NO TSCA 12(B): NO CDTA: NO
 SARA 311/312: ACUTE: YES CHRONIC: NO FIRE: NO PRESSURE: NO
 REACTIVITY: NO (PURE / SOLID)

AUSTRALIAN HAZCHEM CODE: NONE ALLOCATED.
 POISON SCHEDULE: NONE ALLOCATED.

WHMIS: THIS MSDS HAS BEEN PREPARED ACCORDING TO THE HAZARD CRITERIA OF
 THE CONTROLLED PRODUCTS REGULATIONS (CPR) AND THE MSDS CONTAINS
 ALL OF THE INFORMATION REQUIRED BY THE CPR.

16. OTHER INFORMATION

NFPA RATINGS:
 HEALTH: 1 FLAMMABILITY: 0 REACTIVITY: 1

REPORT NUMBER: 703

UNIVAR USA INC.

PAGE: 008

MSDS NO: MZC0357

MATERIAL SAFETY DATA SHEET

MAINFRAME UPLOAD DATE: 03/04/05

VERSION: 004

PRODUCT: CALCIUM CHLORIDE SOLID

ORDER NO: 343354

PROD NO : 743158

----- FOR ADDITIONAL INFORMATION -----

CONTACT: MSDS COORDINATOR

UNIVAR USA INC.

DURING BUSINESS HOURS, PACIFIC TIME

(425)889-3400

06/27/07 08:12

PRODUCT: 743158

CUST NO: 408474

ORDER NO: 343354

----- NOTICE -----

***** UNIVAR USA INC("UNIVAR"), EXPRESSLY DISCLAIMS

ALL EXPRESS OR IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A

PARTICULAR PURPOSE, WITH RESPECT TO THE PRODUCT OR INFORMATION PROVIDED

HEREIN, AND SHALL UNDER NO CIRCUMSTANCES BE LIABLE FOR INCIDENTAL OR

CONSEQUENTIAL DAMAGES. **

DO NOT USE INGREDIENT INFORMATION AND/OR PERCENTAGES IN THIS MSDS AS A
PRODUCT SPECIFICATION. FOR PRODUCT SPECIFICATION INFORMATION REFER TO A PRODUCT
SPECIFICATION SHEET AND/OR A CERTIFICATE OF ANALYSIS. THESE CAN BE OBTAINED FROM
YOUR LOCAL UNIVAR SALES OFFICE.

ALL INFORMATION APPEARING HEREIN IS BASED UPON DATA OBTAINED FROM THE
MANUFACTURER AND/OR RECOGNIZED TECHNICAL SOURCES. WHILE THE INFORMATION IS
BELIEVED TO BE ACCURATE, UNIVAR MAKES NO REPRESENTATIONS AS TO ITS ACCURACY OR
SUFFICIENCY. CONDITIONS OF USE ARE BEYOND UNIVARS CONTROL AND THEREFORE USERS
ARE RESPONSIBLE TO VERIFY THIS DATA UNDER THEIR OWN OPERATING CONDITIONS TO
DETERMINE WHETHER THE PRODUCT IS SUITABLE FOR THEIR PARTICULAR PURPOSES AND THEY
ASSUME ALL RISKS OF THEIR USE, HANDLING, AND DISPOSAL OF THE PRODUCT, OR FROM
THE PUBLICATION OR USE OF, OR RELIANCE UPON , INFORMATION CONTAINED HEREIN.
THIS INFORMATION RELATES ONLY TO THE PRODUCT DESIGNATED HEREIN, AND DOES NOT
RELATE TO ITS USE IN COMBINATION WITH ANY OTHER MATERIAL OR IN ANY OTHER
PROCESS.

* * * E N D O F M S D S * * *